



PARKER FASTENERS LOCK-OUT® HIGH TORQUE DRIVE FOR FLAT HEADS:

CAN BE MADE OUT OF:

- 302 S/S (18-8)
- ALLOY

PART SIZES:

- #6 (1/4- 12 INCH)
- #8 (1/4- 12 INCH)
- #10 (1/4- 12 INCH)
- 1/4 (1/4- 12 INCH)
- 5/16 (1/2- 12 INCH)
- 3/8 (1/2- 10 INCH)
- 7/16 (3/4- 7 INCH)
- 1/2 (1/2- 7 INCH)
- 5/8 (3/4- 7 INCH)

PART SIZES CONT:

- M4 (5MM-120MM)
- M5 (6MM-200MM)
- M6 (6MM-300MM)
- M8 (6MM-300MM)
- M10 (6MM-300MM)
- M12 (6MM-280MM)
- M14 (6MM-220MM)
- M16 (18MM-170MM)

LOCK-OUT®
PATENTED
US 8,992,151

***DIFFERENT HEAD SIZES HAVE DIFFERENT DRIVE CALLOUT



PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF PARKER FASTENERS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF PARKER FASTENERS IS PROHIBITED.

| | | | | | |
|-------------|---------|---|-----------|--------|---------|
| | | UNLESS OTHERWISE SPECIFIED: | | NAME | DATE |
| | | DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± ANGULAR: MACH ± BEND ± TWO PLACE DECIMAL ± THREE PLACE DECIMAL ± | DRAWN | PAUL F | 1/30/14 |
| | | INTERPRET GEOMETRIC TOLERANCING PER: | CHECKED | MATT B | 1/30/14 |
| | | MATERIAL SEE NOTES | ENG APPR. | | |
| | | FINISH | MFG APPR. | | |
| NEXT ASSY | USED ON | | Q.A. | | |
| APPLICATION | | DO NOT SCALE DRAWING | COMMENTS: | | |

| | | |
|---|-----------------------------|--------------|
| PARKER FASTENERS | | |
| TITLE: LOCK-OUT® HIGH TORQUE DRIVE FLAT HEAD SALES PRINT | | |
| SIZE A | DWG. NO. PARKERLOK-INBSC | REV |
| SCALE: 2:1 | WEIGHT: | SHEET 1 OF 1 |